unilli TYRE
www.unilli.com
unilli

unilli

www.unilli.com

04 LIGHT TRUCK RADIAL

05 LIGHT TRUCK BIAS

08 SAND & DESERT

09 INDUSTRIAL

10 TRAILER

11 AGRICULTURAL

13 LAWN, GARDEN & GOLF cart

15 ATV & UTV

18 GO KART

20 MOBILITY

23 WHEELBARROW

COMPANY INTRODUCTION

Acme Rubber Ind. Co., Ltd. a subsidiary of Unilli Motor Co.,Ltd, is a specialized manufacturer of tyres. We produce various kinds and sizes of pneumatic rubber tyres and sell them to all over the world.

Tyre is a capital intensive and technical intensive industry.

Acme Rubber Ind. Co., Ltd has advanced equipments, perfect developments and quality examination and high efficient management. We insist that quality is the most Important thing, and supply customers with the best products. We keep designing new products to meet market demands due to rapidly market change.

Though we are not the most famous tyre manufacturer, we have team of professional technicians & marketing staff and we supply you any product you require. Acme Rubber Ind. Co., Ltd is your best choice.

LIGHT TRUCK

Radial Tire

UN—331

SIZE	Ply Rating	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Load (lbs)	Max. Infl Pressure (PSI)
185R14C	8PR	649	190	5.5	1874	65

UN—332

SIZE	Ply Rating	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Load (lbs)	Max. Infl Pressure (PSI)
195R15C	6PR	693	201	5.5	1929	55

UN—335

SIZE	Ply Rating	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Load (lbs)	Max. Infl Pressure (PSI)
7.00R16 LT	12PR	775	189	5.5	2710	87
7.50R16 LT	12PR	802	206	6.0	3175	95

UN—337

SIZE	Ply Rating	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Load (lbs)	Max. Infl Pressure (PSI)
195/75R16C	10PR	698	193	5.5	2335	76

Bias Tire

UN—301

SIZE	Ply Rating	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Load (lbs)	Max. Infl Pressure (PSI)
7.00-15	10PR	759	195	5.5	2379	76

UN—302

SIZE	Ply Rating	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Load (lbs)	Max. Infl Pressure (PSI)
6.00-14	8PR	681	177	4.5	2379	50

LIGHT TRUCK

Bias Tire

UN—303

SIZE	Ply Rating	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Load (lbs)	Max. Infl Pressure (PSI)
7.00-15	12PR	759	195	5.5	2600	83

UN—305

SIZE	Ply Rating	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Load (lbs)	Max. Infl Pressure (PSI)
5.50-13	8PR	620	164	4.0	1344	62
7.00-16	10PR	783	196	5.5	2491	73
8.25-16	14PR	855	242	6.5	2491	84

UN—306

SIZE	Ply Rating	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Load (lbs)	Max. Infl Pressure (PSI)
6.50-14	8PR	704	180	4.5	1854	60
6.50-16	10PR	746	182	4.5	2226	71
7.00-16	10PR	783	196	5.5	2491	73
7.50-16	14PR	806	214	6.0	3329	94

UN—307

SIZE	Ply Rating	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Load (lbs)	Max. Infl Pressure (PSI)
7.00-16	12PR	783	196	5.5	2709	87

Bias Tire

UN—311

SIZE	Ply Rating	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Load (lbs)	Max. Infl Pressure (PSI)
7.50-16	8PR	808	214	6.0	2590	62

UN—312

SIZE	Ply Rating	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Load (lbs)	Max. Infl Pressure (PSI)
7.50-16	8PR	809	213	6.0	2590	62

SAND & DESERT

UN—321

SIZE	Ply Rating	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Load (lbs)	Max. Infl Pressure (PSI)
9.00-16	8PR	874	274	7.0	2470	45
9.00-17	8PR	874	274	8.0	2910	45
9.00-18	8PR	893	267	8.0	2910	45

UN—322

SIZE	Ply Rating	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Load (lbs)	Max. Infl Pressure (PSI)
9.00-16	8PR	874	274	7.0	2470	45
9.00-17	8PR	890	285	7.5	2910	45

UN—201

SIZE	Ply Rating	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Infl Pressure (PSI)
18x7-8	16PR	440	164	4.25	120
5.00-8	8PR	460	138	3.5	100
21x8-9	14PR	516	190	6	120
6.00-9	12PR	528	151	4.0	100
6.50-10	10PR	585	164	5.0	100
7.00-12	12PR	674	183	5.0	100
7.00-15	14PR	735	192	5.5	110
7.50-16	12PR	807	201	6.0	110
8.15-15 (28x9-15)	14PR	708	198	6.5	110
8.25-15	14PR	848	245	6.5	120

UN—202

SIZE	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Load (lbs)	Max. Infl Pressure (PSI)
10-16.5	10PR	790	266	8.25	50
12-16.5	12PR	834	316	9.75	60

TRAILER

UN—801

SIZE	Ply Rating	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Load (lbs)	Max. Infl Pressure (PSI)
4.80/4.00-8	8PR	401	109	3.0	760	90

UN—802

SIZE	Ply Rating	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Load (lbs)	Max. Infl Pressure (PSI)
5.00-10	8PR	514	142	3.5	947	58

UN—803

SIZE	Ply Rating	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Load (lbs)	Max. Infl Pressure (PSI)
5.00-12	8PR	584	150	3.5	1069	57

UN—305

SIZE	Ply Rating	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Load (lbs)	Max. Infl Pressure (PSI)
5.50-13	8PR	620	164	4.0	1344	62

AGRICULTURAL

UN—101

SIZE	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Load (lbs)	Max. Infl Pressure (PSI)
4.00-6	372	114	3.0	419	40
4.00-8	423	114	3.0	507	40

UN—102

SIZE	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Load (lbs)	Max. Infl Pressure (PSI)
3.50-6	330	90	2.5	364	40
4.00-8	399	112	3.0	340	34
5.00-12	570	139	3.0	771	36

UN—103

SIZE	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Load (lbs)	Max. Infl Pressure (PSI)
3.50-5	308	90	2.5	331	36
3.50-7	362	90	2.5	397	40
4.00-7	419	112	3.0	397	40
5.00-10	518	140	3.5	573	32
5.00-12	570	139	3.0	771	36
5.50-13	625	158	4.0	1364	50
6.00-14	681	182	4.5	1364	50

UN—105

SIZE	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Load (lbs)	Max. Infl Pressure (PSI)
4.80/4.00-8	401	109	3.0	760	60

AGRICULTURAL

UN-106

SIZE	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Infl Pressure (PSI)
20x10.00-10	501	238	8.0	32

UN-801

SIZE	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Load (lbs)	Max. Infl Pressure (PSI)
4.80/4.00-8	401	109	3.0	760	60

UN-802

SIZE	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Load (lbs)	Max. Infl Pressure (PSI)
5.00-10	514	142	3.5	947	43

UN-803

SIZE	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Load (lbs)	Max. Infl Pressure (PSI)
5.00-12	584	150	3.5	1069	57

UN-305

SIZE	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Load (lbs)	Max. Infl Pressure (PSI)
5.50-13	620	164	4.0	1344	62

LAWN, GARDEN & GOLF cart

UN-401

SIZE	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Infl Pressure (PSI)
18x8.50-8	446	226	7.5	30
15x6.00-6	358	158	4.5	35

UN-402

SIZE	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Infl Pressure (PSI)
16x6.50-8	401	175	5.5	28

UN-403

SIZE	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Infl Pressure (PSI)
18x6.50-8	458	190	5.5	40
18x8.50-8	503	232	7.5	30

UN-405

SIZE	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Infl Pressure (PSI)
16x6.50-8	402	174	5.5	28

UN-407

SIZE	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Load (lbs)	Max. Infl Pressure (PSI)
205/65-10	520	210	5.5	916	35

UN-702

SIZE	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Infl Pressure (PSI)
145/70-6	350	136	4.5	4

UN-704

SIZE	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Infl Pressure (PSI)
145/70-6	350	136	4.5	4

UN-711

SIZE	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Infl Pressure (PSI)
19x7.00-8	477	181	5.5	5
18x9.50-8	447	247	8.0	5

UN-712

SIZE	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Infl Pressure (PSI)
18x9.50-8	456	268	8.0	5

UN-713

SIZE	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Load (lbs)	Max. Infl Pressure (PSI)
25x8-12	629	216	7.0	340	7
25x10-12	628	252	7.5	420	7

UN-715

SIZE	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Infl Pressure (PSI)
22x10-9	526	290	8.0	5.0

UN-716

SIZE	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Infl Pressure (PSI)
20x10R9	556	260	8.0	36

UN-717

SIZE	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Infl Pressure (PSI)
120/60-8	338	116	4.0	32

UN-718

SIZE	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Infl Pressure (PSI)
160/40-10	390	148	4.0	32

UN-719R

SIZE	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Infl Pressure (PSI)
16x8.00-7	378	180	5.2	5

UN-722

SIZE	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Infl Pressure (PSI)
19x7.00-8	476	181	5.5	5
21x7-10	533	177	5.5	5

UN-723

SIZE	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Infl Pressure (PSI)
22x9R12	559	227	7.0	7
22x12R12	559	304	9.5	7
26x9R14	660	231	7.0	7
26x11R14	660	280	8.0	7

UN-724

SIZE	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Infl Pressure (PSI)
22x7-10	559	177	5.5	5

UN-726

SIZE	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Infl Pressure (PSI)
22x10-10	559	248	8	5

GO KART

UN—501

SIZE	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Infl Pressure (PSI)
4.10/3.50-4	265	87	2.5	20
11x3.50-5	282	102	3.0	20
11x4.50-5	270	124	4.5	20
11x6.00-5	269	181	6.6	20

UN—503

SIZE	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Infl Pressure (PSI)
10x4.50-5	256	128	4.5	20

UN—505

SIZE	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Infl Pressure (PSI)
10x3.60-5	246	120	4.5	20
11x6.00-5	268	182	6.6	20
11x7.10-5	282	198	6.6	20

UN—556

SIZE	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Infl Pressure (PSI)
110/55R6.5	286	104	2.5	36
90/65R6.5	284	93	2.0	36

UN—505SL

SIZE	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Infl Pressure (PSI)
10.5x4.50-6	258	167	6.6	7
11x6.00-6	268	186	8.0	7
11.5x8.00-6	270	256	10.0	7
12x9.00-6	276	258	10.0	7

DIRT & RAIN KART



UN—506

SIZE	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Infl Pressure (PSI)
11x5.00-5	285	150	4.5	20

UN—508

SIZE	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Infl Pressure (PSI)
12x7.00-6	305	186	8	20
12x8.00-6	305	255	10	20
12x9.00-6	305	258	10	20

UN—519

SIZE	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Infl Pressure (PSI)
10x4.20-5	256	126	4.5	20

UN—520

SIZE	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Infl Pressure (PSI)
11x6.00-5	270	180	6.6	20

UN—521

SIZE	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Infl Pressure (PSI)
12x4.00-5	300	93	2.5	50

MOBILITY

※ Black & Gray Both Available

UN—221

SIZE	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Infl Pressure (PSI)
3.50-5	305	93	2.0	50

UN—222

SIZE	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Infl Pressure (PSI)
4.00--5	323	105	2.0	50

UN—223

SIZE	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Infl Pressure (PSI)
90/70-6	279	93	2.5	32
100/50-6	296	96	2.5	32
100/50-8	312	97	2.5	32
100/60-8	336	88	2.5	32
115/55-8	338	116	4.0	32
90/40-8	284	84	2.5	32
120/70-8	362	120	4.0	32

UN—225

SIZE	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Infl Pressure (PSI)
3.00-4	269	91	2.0	50

UN—226

SIZE	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Infl Pressure (PSI)
2.80/2.50-5	226	70	2.0	50

UN—227

SIZE	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Infl Pressure (PSI)
80/80-8	328	76	2.5	32

UN—228

SIZE	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Infl Pressure (PSI)
90/70-8	327	92	2.5	32

UN—229

SIZE	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Infl Pressure (PSI)
110/50R6.5	276	106	2.0	36

※ Black & Gray Both Available

UN-511

SIZE	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Load (lbs)	Max. Infl Pressure (PSI)
130/90-6	371	139	4.0	453	25

UN-169

SIZE	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Infl Pressure (PSI)
80/80-8 (3.00-8)	338	83	2.0	32

UN-502A

SIZE	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Infl Pressure (PSI)
90/80-8	354	86	2.5	32

UN-168A

SIZE	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Infl Pressure (PSI)
70/65-8	306	80	2.5	32
90/80-8	352	84	2.5	32

UN-7311

SIZE	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Infl Pressure (PSI)
80/65-8	303	85	2.5	32

UN-7101

SIZE	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Load (lbs)	Max. Infl Pressure (PSI)
3.50-8	385	101	3.0	375	36
4.00-8	385	101	3.0	375	36

UN-231

SIZE	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Infl Pressure (PSI)
4.10/3.50-4	267	90	2.5	50
4.10/3.50-5	290	86	2.5	50
4.10/3.50-6	328	94	2.5	50
4.00-6	348	106	2.5	50

UN-232

SIZE	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Infl Pressure (PSI)
2.50-4	220	56	1.5	50

unilli

UNILLI MOTOR CO., LTD. ACME RUBBER IND. CO., LTD.

Factory1：45, Singong 6th Rd., Tianjhong Township, Changhua County 52046,Taiwan
TEL：+886-4-8760061 FAX：+886-4-8760097
E-mail：unilli-tyre1@unilli.com

Factory2：1-6, Douyuan E. Rd., Pitou Township, Changhua County 52345, Taiwan
TEL：+886-4-8877052 FAX：+886-4-8877349
E-mail：unilli-tyre5@unilli.com
www.unilli.com